



MDS45

High capacity with short depth

Due to its low installation depth the MDS 45 is perfectly suited for installation on and under the counter. The MDS 45 is the ideal solution, especially in confined spaces behind the counter.

The drawer pulls out to just 190 mm to provide full access to the cash register insert. This gives staff more room to move behind the often cramped sales counter.

The coin insert with 8 separate coin cups can be removed en bloc. Upright note compartments with pressure plates allow many notes to be stored in each compartment. An universal compartment for receipts and rolls of coins is located below the coin section.

MDS 45 – the first choice for quality-conscious bakeries, food trucks and all applications that require a low pull-out depth.



Closed drawer



Short for small footprints

THE MDS45 AT A GLANCE

- All-steel construction
- 8 weighable coin cups
- Universal compartment under the coin tray
- Cash drawer can be mounted on or under the counter
- Coin tray can be removed en bloc
- Drawer extends only 190 mm



→ **MICROSWITCH**

A microswitch for status enquiry is integrated.

→ **ELECTRICAL CONNECTION OPTIONS**

Compatible with all systems

→ **CONNECTION CABLE**

To be ordered separately: 2m, Epson/RJ12 or SDL

→ **LOCK ON THE CASH DRAWER**

Identical 3-position lock (emergency opening, electrical opening, locked position) incl. 2 locks; random locks on demand.



Empty drawer insert



Filled drawer insert with optional lid

PRODUCT OVERVIEW	MDS45
DIMENSIONS (W X D X H) IN MM CA.	454 x 223 x 124
WEIGHT IN KG CA.	7.8
MATERIAL	All-steel construction
COLOR	Anthracite RAL 7021 ●
NUMBER OF COMPARTMENTS	4 note-, 8 coin-, 1 universal compartment
WEIGHABLE COIN CUPS	Yes
REMOVABLE INSERT	No
ELECTR. VERSION IN VOLTS	6 - 38
INTERFACES	Interface multi 6 - 38 V, separate plug-in cable for connection to common hardware
CABLE	2 m cable // RJ12 (29101.090-0020) 3 m cable // SDL (29101.091-0020)
CLOSURE // TYPE OF CLOSURE	Identical 3-position lock; random locks on demand
DRAWER RUNNERS	Ball bearing mounted rails
LOCKABLE LID	Optional

